OSCA LED SQUARE **7999**

astro

SKU 1252025



PRODUCT SPECIFICATION

GENERAL

FINISH:Matt BlackCABLE LENGTH:Not ApplicableMAIN MATERIAL:Metal - AluminiumGROSS WEIGHT:0.378 (Kg)DIMENSIONS:H: 80mm W: 80mm D: 80mmCLASS:CE (Class I)INSTALLATION ORIENTATION:Ceiling MountIP RATING:IP 20

INSTALLATION ORIENTATION:Ceiling MountIP RATING:IP20CUT OUT HOLE:Not ApplicableBATHROOM ZONE:Zone 3RECESS DEPTH:Not ApplicableVOLTAGE:Mains 230V

FIRE RATING: Not Applicable PRODUCT F MARK: Suitable for mounting on flammable materials

LAMP

LIGHT SOURCE:LED ModuleMACADAM ELLIPSE:3-StepMAXIMUM WATTAGE:7.8WUGR:To Be AdvisedMAXIMUM LAMP LENGTH:Not ApplicableBEAM ANGLE:50 (Degrees)LAMP INCLUDED?Yes (Integral)TILT ADJUSTMENT ANGLE:Not Applicable

LAMP INCLUDED?Yes (Integral)TILT ADJUSTMENT ANGLE:Not ApplicableLUMINOUS FLUX:506.52 (Im)ROTATION ADJUSTMENT ANGLE:Not ApplicableCOLOUR TEMP:2700 (K)AVERAGE LIFESPAN:40,000 (Hrs)CRI:80L70:To Be Advised

R9: -1.0

ELECTRICAL

SWITCHED: No SUPPLY FREQUENCY: 50/60 (Hz)

DIMMABLE: Yes DRIVER/BALLAST VOLTAGE: 210-250 (V)

DIMMING METHOD: Phase - Leading & Trailing Edge DRIVER AVERAGE LIFESPAN: 40000 (Hrs)


DRIVER OUTPUT CURRENT:Not ApplicableEFFICACY:64.94 (lm/W)DRIVER OUTPUT VOLTAGE:Not ApplicableDRIVER/BALLAST INCLUDED?Yes (Integral)


ADDITIONAL INFORMATION





BOX QUANTITY x 20





T: +44 (0) 1279 427001 sales@astrolighting.com www.astrolighting.com www.astrolighting.com