

# APRILIA TWIN ADJUSTABLE 5749

SKU 1256019

astro



## PRODUCT SPECIFICATION

### GENERAL

|                                  |                          |                        |  |
|----------------------------------|--------------------------|------------------------|--|
| <b>FINISH:</b>                   | Matt White               | <b>CABLE LENGTH:</b>   | 450 (mm)                                     |
| <b>MAIN MATERIAL:</b>            | Metal - Aluminium        | <b>GROSS WEIGHT:</b>   | 0.678 (Kg)                                   |
| <b>DIMENSIONS:</b>               | H: 180mm W: 95mm D: 69mm | <b>CLASS:</b>          | CE (Class III)                               |
| <b>INSTALLATION ORIENTATION:</b> | Ceiling Mount            | <b>IP RATING:</b>      | IP21   |
| <b>CUT OUT HOLE:</b>             | L: 165mm W: 85mm         | <b>BATHROOM ZONE:</b>  | Zone 3                                       |
| <b>RECESS DEPTH:</b>             | Not Applicable           | <b>VOLTAGE:</b>        | Constant Current 350 (mA)                    |
| <b>FIRE RATING:</b>              | Not Applicable           | <b>PRODUCT F MARK:</b> | Suitable for mounting on flammable materials |

### LAMP

|                             |                |                                   |                |
|-----------------------------|----------------|-----------------------------------|----------------|
| <b>LIGHT SOURCE:</b>        | COB LED        | <b>MACADAM ELLIPSE:</b>           | 3-Step         |
| <b>MAXIMUM WATTAGE:</b>     | 2 x 6.1W       | <b>UGR:</b>                       | To Be Advised  |
| <b>MAXIMUM LAMP LENGTH:</b> | Not Applicable | <b>BEAM ANGLE:</b>                | 36.1 (Degrees) |
| <b>LAMP INCLUDED?</b>       | Yes (Integral) | <b>TILT ADJUSTMENT ANGLE:</b>     | 35 (Degrees)   |
| <b>LUMINOUS FLUX:</b>       | 1206.1 (lm)    | <b>ROTATION ADJUSTMENT ANGLE:</b> | 360 (Degrees)  |
| <b>COLOUR TEMP:</b>         | 3000 (K)       | <b>AVERAGE LIFESPAN:</b>          | 36,300 (Hrs)   |
| <b>CRI:</b>                 | 80             | <b>L70:</b>                       | To Be Advised  |
| <b>R9:</b>                  | 13.0           |                                   |                |

### ELECTRICAL

|                               |                        |                                 |                |
|-------------------------------|------------------------|---------------------------------|----------------|
| <b>SWITCHED:</b>              | No                     | <b>SUPPLY FREQUENCY:</b>        | Not Applicable |
| <b>DIMMABLE:</b>              | Yes                    | <b>DRIVER/BALLAST VOLTAGE:</b>  | Not Applicable |
| <b>DIMMING METHOD:</b>        | Control Gear Dependant | <b>DRIVER AVERAGE LIFESPAN:</b> | Not Applicable |
| <b>DRIVER OUTPUT CURRENT:</b> | Not Applicable         | <b>EFFICACY:</b>                | 97.27 (lm/W)   |
| <b>DRIVER OUTPUT VOLTAGE:</b> | Not Applicable         | <b>DRIVER/BALLAST INCLUDED?</b> | No             |

## ADDITIONAL INFORMATION

CE



BOX QUANTITY x 20

PRODUCT ELEVATIONS

