
ENNA RECESS SWITCHED 8039

astro

SKU 1058064



PRODUCT SPECIFICATION

GENERAL

FINISH: Polished Chrome CABLE LENGTH: Not Applicable MAIN MATERIAL: Metal - Aluminium GROSS WEIGHT: 0.7 (kg)

DIMENSIONS: H:110mm W: 97.5mm D:132mm CLASS: CE (Class I)

 INSTALLATION ORIENTATION:
 Wall Mount
 IP RATING:
 IP20

 CUT OUT HOLE:
 Ø: 51mm/2"
 BATHROOM ZONE:
 Zone 3

 RECESS DEPTH:
 75mm
 VOLTAGE:
 Mains 230V

FIRE RATING: Not Applicable PRODUCT F MARK: Suitable for mounting on flammable materials

LAMP

LIGHT SOURCE:High-Power LEDMACADAM ELLIPSE:3-Step

MAXIMUM WATTAGE:2WUGR:Not ApplicableMAXIMUM LAMP LENGTH:Not ApplicableBEAM ANGLE:18 (Degrees)

LAMP INCLUDED? Yes TILT ADJUSTMENT ANGLE: 90 (Degrees) **LUMINOUS FLUX:** 151 (lm) ROTATION ADJUSTMENT ANGLE: 330 (Degrees) **COLOUR TEMP:** AVERAGE LIFESPAN: 2700 (K) 60,000 (Hrs) CRI: 80 L70: Not Applicable

R9: 8

ELECTRICAL

SWITCHED: SUPPLY FREQUENCY: Yes 50/60 (Hz) DIMMABLE: No DRIVER/BALLAST VOLTAGE: 100-240 (V) DIMMING METHOD: Not Applicable DRIVER AVERAGE LIFESPAN: 30,000 (Hrs) **DRIVER OUTPUT CURRENT:** 700 (mA) EFFICACY: 39 (lm/W)


DRIVER OUTPUT VOLTAGE: Not Applicable DRIVER/BALLAST INCLUDED? Yes


ADDITIONAL INFORMATION





BOX QUANTITY X8

CE









T: +44 (0) 1279 427001 F: +44 (0) 1279 427002 sales@astrolighting.com www.astrolighting.com