ENNA RECESS SWITCHED 8016 SKU 1058062



PRODUCT SPECIFICATION


GENERAL


FINISH:	Painted White	CABLE LENGTH:	Not Applicable
MAIN MATERIAL:	Metal - Aluminium	GROSS WEIGHT:	0.7 (kg)
DIMENSIONS:	H:110mm W:97.5mm D:132mm	CLASS:	CE (Class I)
INSTALLATION ORIENTATION:	Wall Mount	IP RATING:	IP20
CUT OUT HOLE:	Ø: 51mm/2″	BATHROOM ZONE:	Zone 3
RECESS DEPTH:	75mm	VOLTAGE:	Mains 230V
FIRE RATING:	Not Applicable	PRODUCT F MARK:	Suitable for mounting on flammable materials
LAMP			
LIGHT SOURCE:	High-Power LED	MACADAM ELLIPSE:	3-Step
MAXIMUM WATTAGE:	2W	UGR:	Not Applicable
MAXIMUM LAMP LENGTH:	Not Applicable	BEAM ANGLE:	18 (Degrees)
LAMP INCLUDED?	Yes	TILT ADJUSTMENT ANGLE:	90 (Degrees)
LUMINOUS FLUX:	151 (lm)	ROTATION ADJUSTMENT ANGLE:	330 (Degrees)
COLOUR TEMP:	2700 (K)	AVERAGE LIFESPAN:	60,000 (Hrs)
CRI:	80	L70:	Not Applicable
R9:	8		
ELECTRICAL			
SWITCHED:	Yes	SUPPLY FREQUENCY:	50/60 (Hz)
DIMMABLE:	No	DRIVER/BALLAST VOLTAGE:	100-240 (V)
DIMMING METHOD:	Not Applicable	DRIVER AVERAGE LIFESPAN:	30,000 (Hrs)
DRIVER OUTPUT CURRENT:	700 (mA)	EFFICACY:	39 (lm/W)
DRIVER OUTPUT VOLTAGE:	Not Applicable	DRIVER/BALLAST INCLUDED?	Yes
ADDITIONAL INFORM	MATION		C





BOX QUANTITY X8

PRODUCT ELEVATIONS









T: +44 (0) 1279 427001

F: +44 (0) 1279 427002

INTERIOR LIGHTING PAGE. 01/02