LEROS TRIMLESS 7418

astro

SKU 1342002



PRODUCT SPECIFICATION

GENERAL

FINISH:Matt WhiteCABLE LENGTH:MAIN MATERIAL:Metal - ZincGROSS WEIGHT:

DIMENSIONS:H:90mm W:90mm D: 42mmCLASS:CE (Class III)INSTALLATION ORIENTATION:Wall MountIP RATING:IP20

INSTALLATION ORIENTATION: Wall Mount IP RATING: IP20

CUT OUT HOLE: L: 75mm W: 45mm BATHROOM ZONE: Zone 3

RECESS DEPTH: 45 (mm) VOLTAGE: Constant current 350mA FIRE RATING: Not Applicable PRODUCT F MARK: Suitable for mounting on flammable materials

LAMP

LIGHT SOURCE:High Power LEDMACADAM ELLIPSE:To Be AdvisedMAXIMUM WATTAGE:1WUGR:Not Applicable

MAXIMUM WATTAGE:1WUGR:Not ApplicableMAXIMUM LAMP LENGTH:Not ApplicableBEAM ANGLE:Not ApplicableLAMP INCLUDED?Yes (Integral)TILT ADJUSTMENT ANGLE:Not Applicable

LUMINOUS FLUX:35.6 (lm)ROTATION ADJUSTMENT ANGLE:Not ApplicableCOLOUR TEMP:2700KAVERAGE LIFESPAN:36,300 (Hrs)CRI:80L70:To Be Advised

R9: 6.0

ELECTRICAL

SWITCHED:NoSUPPLY FREQUENCY:Not ApplicableDIMMABLE:YesDRIVER/BALLAST VOLTAGE:Not ApplicableDIMMING METHOD:Control Gear DependentDRIVER AVERAGE LIFESPAN:Not Applicable

DIMMING METHOD: Control Gear Dependent DRIVER AVERAGE LIFESPAN: Not Applicable

DRIVER OUTPUT CURRENT: Not Applicable EFFICACY: 32.36 (Im/W)

DRIVER OUTPUT VOLTAGE: Not Applicable DRIVER/BALLAST INCLUDED? No

ADDITIONAL INFORMATION

POV QUANT

Not Applicable

0.21 (Kg)

BOX QUANTITY x 50

CE



