astro



PRODUCT SPECIFICATION

GENERAL

White FINISH: CABLE LENGTH: Not Applicable MAIN MATERIAL: Metal - Aluminium **GROSS WEIGHT:** 0.72 (kg) H:100mm W:70mm D:100mm DIMENSIONS: CLASS: CE (Class I) INSTALLATION ORIENTATION: Wall Mount - Vertical IP RATING: IP65

CUT OUT HOLE:Not ApplicableBATHROOM ZONE:Not ApplicableRECESS DEPTH:Not ApplicableVOLTAGE:Mains 230V

FIRE RATING: Not Applicable PRODUCT F MARK: Suitable for mounting on flammable materials

LAMP

LIGHT SOURCE: High Power LED MACADAM ELIPSE: 3-Step MAXIMUM WATTAGE: 3W Max UGR: Not Applicable MAXIMUM LAMP LENGTH: Not Applicable **BEAM ANGLE:** Not Applicable LAMP INCLUDED? Yes (Integral) TILT ADJUSTMENT ANGLE: Not Applicable **LUMINOUS FLUX:** 47.08 (lm) **ROTATION ADJUSTMENT ANGLE:** Not Applicable **COLOUR TEMP:** AVERAGE LIFESPAN: 3000 (K) To Be Advised CRI: 80 L70: To Be Advised

ELECTRICAL

R9:

SWITCHED: SUPPLY FREQUENCY: 50/60 (Hz) No DIMMABLE: No DRIVER/BALLAST VOLTAGE: 220-240 (V) DIMMING METHOD: Not Applicable DRIVER AVERAGE LIFESPAN: 60,000 (Hrs) **DRIVER OUTPUT CURRENT:** 700 (mA) EFFICACY: 12.42 (lm/W) DRIVER OUTPUT VOLTAGE: DRIVER/BALLAST INCLUDED? Not Applicable Yes (Integral)

ADDITIONAL INFORMATION

25.4


BOX QUANTITY X 6





1000 HOURS SALT-SPRAY TESTED




Œ









T: +44 (0) 1279 427001 F: +44 (0) 1279 427002 sales@astrolighting.com www.astrolighting.com